Chaparral Energy Monitor Well Construction Diagram OWRB WELL ID NUMBER 72860 **Legal Description** Quarters ___NE-NE-SW Well # MW - 28 Section <u>02</u> Township <u>27N</u> Range <u>05E1</u> WELL COVER / CASING PROTECTOR 8 5/8" steel casing FROM <u>+3'</u> TO <u>2'</u> ground level -SURFACE SEAL & PAD Concrete FROM +3' TO 2'ANNULAR SEAL Neat Cement WELL CASING 4" sch 40 PVC FROM 2' TO 163' FROM <u>+2'</u> TO <u>180'</u> FILTER PACK SEAL Bentonite Chips FROM 163' TO 168' FILTER PACK Sand 10 - 20 Coarse SCREEN 4" sch 40 PVC Factory Slotted - .020 inch FROM 168' TO 212' FROM 180' TO 200' Sump_4" sch 40 PVC sump w/bottom cap□ FROM <u>200'</u> TO <u>210'</u> Backfill Bentonite Chips FROM 212' TO 260' Associated Environmental Industries, Corp P.O. Box 5306 Norman, Ok. 73070 (405)360-1434 Office / (405)360-1480 Fax Email: robert@aei-corp.co TOTAL DEPTH OF WELLBORE __260' www.aei-corp.com 7.25" Borehole